




# BLUETTI B300K

The Battery Pack That Does More

2764.8Wh



Renewable



Versatile



Durable



Eco-friendly



## Great Compatibility for More Possibilities

The B300K seamlessly integrates with APEX 300, AC200L, AC200MAX, AC300, and AC500 power stations, giving you the flexibility to scale your energy setup as your needs grow. Whether you're prepping for more power at home or gearing up for your next adventure, the B300K has you covered.

	Apex 300	AC200L	AC200MAX	AC300	AC500
Starting Capacity (Wh)	2,764.8	2,048	2,048	/	/
Expansion Batteries Supported (Single Unit, Wh)	1-6	1-2	1-2	1-4	1-6
Battery Expansion Cable	1 / 2	2	2	2	3
Max Capacity (Single Unit, Wh)	19353.6	7,577	7,577	11,059.2	16588.8
Parallel Connection	3	/	/	2	2
Expansion Batteries Supported (Parallel Setup)	18	/	/	8	12
Max Capacity (Parallel Setup, Wh)	58kWh	/	/	22.1kWh	33.1kWh

### Battery expansion cable



- 1 CA90 battery expansion cable



- 2 P090A/D battery expansion cable



- 3 P090D to P150D battery expansion cable

### Fast Charging

**45 min to 80%**  
Charging with AC300/AC500 using 30A AC charging cable

### Modular and Expandable

**19.3kWh Max.**

### Heat Dissipation

### Safe and Durable

Upgraded LiFePO<sub>4</sub> Cells

### Mix and Match

### 4,000+ Charge Cycles

### A Decade of Lifespan

### 3+1 Years Warranty

### Specifications

Capacity	2,764.8Wh
Type	LiFePO <sub>4</sub> (Lithium Iron Phosphate)
Life Cycles	4,000+
Shelf-life	Recharge to 80% every 3-6 months
USB-A Port	1* 5V/2.4A, 12W
Charging Current	60A Max.

(May decrease outside specified temperatures)  
Note: Connect to power stations for charging  
(Keep batteries and power stations at the same battery level)

Weight	29.5kg / 65.04lbs
Dimensions (L × W × D)	52.5 × 32.7 × 20.0 cm / 20.67 × 12.87 × 8.23in
Charging Temperature	0°C to 40°C / 32°F to 104°F
Operating Temperature	-20°C to 40°C / -4°F to 104°F
Working Humidity	5% to 95% RH
Warranty	3+1 years

\*Specifications are subject to change without further notice.

