



FUTURE-PROOFED EV CHARGING, BUILT TO LAST

CHARGESTORM® CONNECTED 3 combines today's smart charging with the technology needed for tomorrow's EV energy ecosystem. It's the latest update in our award-winning CHARGESTORM® CONNECTED series, designed for easy installation and enhanced control.

EV CHARGING REDEFINED

The CC3, our latest model, is versatile with options for dual or single outlets, with or without fixed cables, all offering up to 22kW of charging power. Designed for 'Plug & Charge', it's cyber-secure and physically tamper-proof. With built-in WiFi, it manages back-end connection and load balancing for efficient EV charging. CC3 connects via an optional 4G-modem when no WiFi is available and uses dual Ethernet ports for easier installation. CC3 is compatible with various third-party backend systems by OCPP and prepared for V2G and V2X technologies.

INSTALLATION MADE SIMPLE

CC3 is tailored for both users and installers. As a standout in our CHARGESTORM® CONNECTED series, it's engineered for effortless installation and user experience. Ideal for diverse installation settings, including B2B environments and destination charging locations, it features efficient punch-out holes for a seamless setup. Dual Ethernet ports allows for speedy and straightforward cabling. Additionally, CC3 offers free training for installers and adheres to international standards.

- Up to 2x22 kW charging capacity, with dual outlets
- Built-in WiFi for easier installation, wireless load balancing and online support
- Ready for the 'Plug & Charge' standard EV drivers want when using public charging
- Daisy chain power and network cabling for easier, quicker and cheaper multi-outlet installations
- Prepared for ISO 15118 and OCPP 2.0.1 – the industry's newest open communication standards
- Adaptable for diverse applications
- Variety of connectivity options

*You might have noticed that we call the Chargestorm Connected an 'EV charger'. Technically speaking it's 'electrical vehicle supply equipment' (or EVSE for short), that provides a safe supply of electricity to power the on-board battery charger in your Electrical Vehicle (EV). Most people use the term EV charger, so to keep things simple, we've chosen to use this term too.

VERSION	3
ARTICLE NUMBER	40-647
CHARGING METHOD	Mode 3
CHARGING CATEGORY	AC charging
OUTLET	Dual type 2 outlets
LOCKING ACTUATOR (TYPE 2 OUTLET)	Yes (Solenoid)
POSITIONING	Wall mounting (standard), pole mount (option)
LOAD BALANCING	Load balancing (NANOGRID™ Internal) is included between the dual outlets of the EVSE, Options for other load balancing solutions between several units (NANOGRID™ HOME, NANOGRID™ AIR, NANOGRID™ CGC).
ENERGY METER	MID approved
NUMBER OF PHASES	3 Phase
CHARGING CURRENT	32 A
FUSE	32 A per outlet
CHARGING CAPACITY	Up to 2 x 22 kW
FREQUENCY	50 Hz
RATED VOLTAGE (INPUT)	400 V
RATED POWER (INPUT)	Up to 2 x 22 kW
POWER INPUT CONNECTOR	up to 25 mm ² terminal blocks
AMBIENT OPERATING TEMPERATURE	-30 °C to +50 °C
RELATIVE HUMIDITY	Up to 100% at 25 °C
WEIGHT	Up to 24 kg
ENCLOSURE DIMENSIONS (L X W X H)	160 x 282 x 449 mm
ENCLOSURE MATERIAL	Plastic, Metal
ENCLOSURE COLOR	Black
ENCLOSURE LOCK	Key
GROUND FAULT DETECTION	MRCDD TYPE B 30mA AC, 30mA DC
GROUND FAULT RESET	Semi-automatic
AUTHENTICATION	RFID, APP, Autocharge
RFID READER	Yes
RFID TAG STANDARD	ISO15693, ISO14443A (MIFARE)
COMMUNICATION PROTOCOL	OCPP 1.6/OCPP 2.0.1**
USER INTERFACE	LED symbols
CONNECTIVITY	4G (optional), 2 x Ethernet, Wi-Fi
APP SUPPORT	OCPP - Third party
COMPLIANCE	RED, IEC 62196, CE, IEC 61851-1
APPROVAL	Download the Declaration of Conformity from WWW.CTEK.COM
DEGREE OF PROTECTION	IP54
IMPACT PROTECTION	IK10
EICHRECHT COMPLIANCE	Yes**
CYBER SECURITY	Yes
ISO 15118	15118-2 EIM
DAISY CHAINING	Power, Network
WARRANTY	5 years

MOUNTING AND CONNECTION

CHARGESTORM® CONNECTED 3 can be easily mounted on a wall with just 4 screws. It can also be mounted on a standard 60 mm pole (option) by attaching the mounting plate to the back of the EVSE. If you need to fit dual EVSE, we also supply a bracket that can handle two EVSE back to back and up to four charging outlets. The pole bracket also allows you to sew both feed and Ethernet cables directly inside it for a tidy and secure installation.

GUARANTEED QUALITY WITH CTEK

Quality is at the heart of everything we do, with safety, simplicity and flexibility characterizing all of our products and solutions. If you have any questions about our products, or would like further information about EV charging, our Customer Support Team is here to help. We are the global leader in battery management solutions, and supply products to more than 70 countries throughout the world. CTEK is also a reliable OEM supplier to many of the world's most prestigious vehicle manufacturers.

For more information visit WWW.CTEK.COM

**Will be supported in coming releases.